

PROUDLY MADE IN USA AT AN ISO 9001 CERTIFIED FACILITY
BUFF CONCRETE SEALER X-5
WATER BASED

Forms a satin water and stain repellent barrier on concrete, masonry and brick surfaces.

DIRECTIONS: CLEAN AREA TO BE DYED AND DRY. TEST WITH A FEW DROPLETS OF WATER AND MAKE SURE THEY ABSORB WITHIN 30 SECONDS, IF THEY DO NOT THEN ACID ETCHING IS REQUIRED BEFORE DYEING. THIS PRODUCT MUST BE CONTINUALLY AGITATED BEFORE AND DURING USE TO MAINTAIN UNIFORMITY OF COLOR. EXACT COLOR WILL VARY DEPENDING ON POROSITY AND EXACT MIX PROPERTIES OF CEMENTOUS SURFACE. WE STRONGLY RECOMMEND DYEING A SMALL INCONSPICUOUS SPOT FIRST TO ENSURE SATISFACTION OF COLOR AND THAT A GOOD BOND CAN BE ACHIEVED. PLEASE NOTE THAT THIS IS A TRANSPARENT DYE, AND WILL NOT HIDE IMPERFECTIONS ON THE SURFACE OF THE CONCRETE. SURFACE MUST BE CLEAN AND DRY BEFORE APPLICATION. NEW CONCRETE MUST HAVE CURED FOR AT LEAST 30 DAYS BEFORE APPLYING DYE. SOME LOOSE RESIDUAL COLOR MAY REMAIN UNBONDED ON THE SURFACE ON LESS POROUS CONCRETE. APPLY FIRST COAT AND ALLOW TO DRY FOR 4 TO 6 HOURS BEFORE APPLYING SECOND COAT. DO NOT ALLOW RAIN OR ANY MOISTURE ON DYED SURFACE BEFORE SEALING. APPLY DYE ONLY USING A SPRAYER WITH A CONICAL TIP WITH A FINE MIST. DO NOT ALLOW ANY POOLING OF THE DYE AS THIS WILL MAKE A DARK SPOT AND WILL NOT BE BONDED. POOLED DYE SHOULD BE SPONGED UP IMMEDIATELY WHILE WET. AGITATE MIXTURE VERY WELL BEFORE BEGINNING APPLICATION AND REGULARLY DURING. HOLD SPRAYER AT AN ANGLE TO PREVENT PULLING UP ANY SETTLED COLOR INTO SPRAYER. ALWAYS WEAR SPIKED SHOES WHEN WALKING ON FRESHLY DYED SURFACE. DO NOT APPLY TOO HEAVILY. IT IS NORMAL TO NOT SEE A STRONG COLORING ON THE FIRST COAT. THIS IS DUE TO THE PENETRATION OF THE DYE INTO THE PORES. THE SECOND COAT WILL BE MARKEDLY STRONGER, SO DON'T APPLY THE FIRST COAT TOO HEAVILY TRYING TO ACHIEVE DESIRED SHADE.

1. FIRST AID:

Eyes – Flush with cool water for at least 15 minutes. Call a physician.

Skin - Wash thoroughly with soap and water. Call a physician.

Ingestion – Call a physician. Never give anything by mouth to an unconscious person.

Inhalation – If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Call a physician.

2. SPILL CONTROL: Eliminate all ignition sources and keep public away. Recover free product with absorbent materials and dispose of in accordance with local, State and Federal Regulations. Keep product out of sewers and water courses.

DANGER: Keep out of reach of children and animals.

Always wear gloves and protective goggles when using this product.

HMIS: H=1, F=0, R=0, PP=X

NET CONTENTS: 5 Gallons (18.9L)

3. PROTECTIVE EQUIPMENT: Wear safety glasses or goggles and recommended protective gloves. If exposure exceeds TLV, wear NIOSH/MSHA approved respirator.

4. PRECAUTIONS: Do not get in eyes, on skin or clothing. Do not take internally. Wash thoroughly after handling.

5. GENERAL INSTRUCTIONS: Before using this product read Material Safety Data Sheet (MSDS) which is available on website.

Note: Emptied Container retains vapor or product residue.

DISCLAIMER: The information contained herein is based on data available to us and is believed to be accurate. However, Stone Technologies, Corp makes no express or implied warranty of merchantability or fitness for a particular use. Handling, storage and use of this product by the buyer or user are beyond the control of Stone Technologies, Corp. Risks such as ineffectiveness or other unintended consequences resulting from but not limited to failure to follow label directions will be assumed by the buyer or user. In no case will seller be held liable for consequential, special or indirect damages resulting from the handling, storage or use of this product. VER 15/10