

***PROUDLY MADE IN USA AT AN ISO 9001 CERTIFIED FACILITY***

# **RX-1 REPAIR AND SEAL**

**Directions:** Concrete surfaces to be treated must be free of foreign material and have an open pore texture. Smooth concrete must be sandblasted or acid etched. Rout out cracks or holes to a depth of 1 inch (25mm) to form a square shaped space (not a “V” shape). To plug a hole or to patch an area mix 3.5 parts RX-1 Repair and Seal with 1 part by volume water and mix to a stiff putty consistency. Water temperature should be 60-70°F (15-20°C). Do not mix more product that can be used in 3 minutes. Form a plug in a gloved hand and press the mixture into the cavity and press hard until the mixture hardens. When sealing cracks start at the highest point and work down. When there is a high volume of water flow due to extreme hydrostatic pressure, a bleeder hose may be necessary to relieve the water pressure while sealing the repair area. This is done by chiseling out the area at the point of greatest water flow and place a stiff section of hose or pipe and secure in place with above mixture. Allow a minimum of 24 hours for hardening. Remove bleeder hose and plug remaining hole.

## **1. FIRST AID:**

**Eyes** – Flush with cool water for at least 15 minutes. Call a physician.

**Skin** - Wash thoroughly with soap and water. Call a physician.

**Ingestion** – Call a physician. Never give anything by mouth to an unconscious person.

**Inhalation** – If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Call a physician.

**2. SPILL CONTROL:** Eliminate all ignition sources and keep public away. Recover free product with absorbent materials and dispose of in accordance with local, State and Federal Regulations. Keep product out of sewers and water courses.

**DANGER:** Keep out of reach of children and animals. Always wear gloves and protective goggles when using this product.

HMIS: H=2, F=0, R=0, PP=X

**NET CONTENTS: 60 Pounds**

**3. PROTECTIVE EQUIPMENT:** Wear safety glasses or goggles and recommended protective gloves. If exposure exceeds TLV, Wear NIOSH/MSHA approved respirator.

**4. PRECAUTIONS:** Do not get in eyes, on skin or clothing. Do not take internally. Wash thoroughly after handling.

**5. GENERAL INSTRUCTIONS:** Before using this product read Material Material Safety Data Sheet (MSDS) which is available on website.

**Note: Emptied Container retains vapor or product residue.**

**DISCLAIMER:** The information contained herein is based on data available to us and is believed to be accurate. However, Stone Technologies, Corp makes no express or implied warranty of merchantability or fitness for a particular use. Handling, storage and use of this product by the buyer or user are beyond the control of Stone Technologies, Corp. Risks such as ineffectiveness or other unintended consequences resulting from but not limited to failure to follow label directions will be assumed by the buyer or user. In no case will seller be held liable for consequential, special or indirect damages resulting from the handling, storage or use of this product. VER 1/2015